A rigorous collection.

# Nut harvester



- **High workflow.**
- **Clean fruit harvest.**
- **High manoeuvrability in the orchard.**

**LEGER SAS** • Z.A. Jean Lagnel • 47290 CANCON • FRANCE
**+33 (0)5 53 01 72 34** contact@legersas.com www.legersas.com

# Nut harvester

| | |
|---|---|
| **Operating speed** | Up to 4km/h - 10 ha/day. |
| **Tractor power** | 70 HP mini. |
| **Power** | **Mechanical:** tractor PTO *(540 rpm max.)*.<br>**Hydraulic:** tractor-powered - 30L/mn with free return flow - on-board hydraulic power unit powered by the PTO shaft.<br>**Electric:** 3-pin tractor plug - 12 VDC *(volt direct current)*. |
| **Collection** | Pick Up roller with combs and rubber bands diameter 930 mm.<br>Rotative side brushe - driven by hydraulic engines.<br>Pick-up width 933 mm. |
| **Cleaning** | 6-blade anti-abrasion extractor on the pick up roller.<br>Blower on conveyor belt with open bars on both sides, flow rate 240m3/hour. |
| **Conveying** | 12 mm slatted conveyor belt driven by hydraulic engine with speed regulation - cleaning brush return of the belt. |
| **Nut storage** | Self-supported tipper 2,7m3 - hydraulic cylinder-operated lift - emptying height at 2m70 - Nut emptying by hydraulic cylinder-operated hatch. |
| **Control command** | Movable electric button box *(magnet or suction)*. |
| **Transport** | Rear 3-point linkage mounted on drawbar.<br>Front tyres: 26x12.00-12 Tubeless 8 ply.<br>Rear tyres : 31x15.50-15 Tubeless 8 ply.<br>Braked directional rear axle.<br>Approval for road use. |
| **Dimensions, weight** | L=6m660; W=2m360; H=2m060.<br>Weight = 3060 kg. |
| **Options** | Scatterer.<br>Carpet lighting.<br>Control cameras. |



